


# REFERENCE SPECIFICATIONS

	SHEET			TILE			
	SPECIFICATIONS	FOUNDATIONS	FLOR-EVER PLUS	CHOICES	ALTERNATIVES	TT SERIES	CX SERIES
Approx.Installed Cost Per Square Foot	\$3.00 - \$3.50		\$3.00 - \$3.50	\$1.50 - \$2.00		\$1.35 - \$2.00	\$1.35 - \$2.00
Colors Available	17	6	30	6	46	7	4
Width	6 ft.		12 ft.	12" x 12" (305mm x 305mm)			
Length	Up to 120'			—			
Gauge – Overall	.080" (2.03mm)	.080" nominal (2.03mm)		1/8" (3.2mm)		3/32" (2.4mm)	.100" (2.5mm)
Vinyl Composition Wearlayer	.050" (1.28mm)	—		—		—	—
Vinyl Wearlayer	—	.020" (.51mm)		—		—	—
Packing	—			45 pcs. (45 sq. ft.; 4.2 sq. meters)			
REFERENCE SPECIFICATIONS • ASTM F 1303	Type II, Grade 1 Class A backing		Type I, Grade 1 Class A backing	—			
• ASTM F 1066	—			Class 2		Class 2**	
FIRE TEST DATA • ASTM E 648; NFPA-253; Critical Radiant Flux - 0.45 watts/cm <sup>2</sup> or greater	YES						
• ASTM E 662; NFPA-258; NBS Smoke Density - 450 or less	YES						
• D.O.T. Motor Vehicle Safety Standard 302	YES			—			
FloorScore Certified for Indoor Air Quality Performance 	YES*						
Static Load Limit	500 psi**		175 psi	250 psi			
HUD/FHA Minimum Property Standards	YES					YES***	
Recommended Subfloor	Suspended wood, concrete, all grade levels						
Installation Method	Full Spread						
Recommended Congoleum Adhesive	3044			AD42			
Seam Sealer	SU80 or SU92 Seam Sealer			—			
Heat Weldable Seams	YES		—	—			
Warranty	Five-Year Commercial Limited Warranty						
Durability	Excellent						
Ease of Maintenance	Excellent						

\* FloorScore certified hard surface flooring products are an alternative compliance to LEED credit EQ4.3 Low-Emitting Materials: Carpet Systems.

\*\* Modified ASTM F 970

\*\*\* When .100" gauge is specified.